



# **Penetration Response of Ultra-High Performance Concrete (UHPC) under Projectile Impact**

**Jian LIU**

A thesis submitted in fulfilment of the requirements for the degree  
of Doctor of Philosophy

School of Civil and Environmental Engineering  
Faculty of Engineering and Information Technology  
University of Technology Sydney, Australia

September 2018

## **CERTIFICATE OF ORIGINAL AUTHORSHIP**

I, Jian Liu declare that this thesis is submitted in fulfilment of the requirements for the award of Doctor of Philosophy, in the Faculty of Engineering and Information Technology at the University of Technology Sydney.

This thesis is wholly my own work unless otherwise reference or acknowledged. In addition, I certify that all information sources and literature used are indicated in the thesis.

This document has not yet been submitted for qualification at any other academic institution.

Print Name: Jian LIU

Signature: Production Note:  
Signature removed prior to publication.

Date: 03-September-2018

## TABLE OF CONTENTS

<b>CERTIFICATE OF ORIGINAL AUTHORSHIP .....</b>	<b>I</b>
<b>TABLE OF CONTENTS.....</b>	<b>II</b>
<b>LIST OF FIGURES .....</b>	<b>VIII</b>
<b>LIST OF TABLES .....</b>	<b>XVI</b>
<b>ABSTRACT .....</b>	<b>1</b>
<b>ACKNOWLEDGEMENTS.....</b>	<b>3</b>
<b>LIST OF PUBLICATIONS.....</b>	<b>4</b>
<b>CHAPTER 1: INTRODUCTION.....</b>	<b>5</b>
1.1 Background information .....	5
1.2 Research goals.....	8
1.3 Outlines .....	10
References .....	11
<b>CHAPTER 2: NUMERICAL STUDY OF ULTRA-HIGH PERFORMANCE CONCRETE UNDER NON-DEFORMABLE PROJECTILE PENETRATION ..</b>	<b>16</b>
Abstract .....	16
2.1 Introduction .....	17
2.2 Finite element model validation.....	18
2.2.1 Mix design of UHPC samples.....	19
2.2.2 Uniaxial compression test .....	19
2.2.3 Four-point bending test .....	21
2.3 Numerical simulation of UHPC targets against projectile penetration.....	22
2.3.1 Projectile .....	23
2.3.2 UHPC targets .....	24
2.3.3 Strain rate effect .....	28
2.3.4 Simulation data .....	29
2.4 Results and discussions.....	30
2.4.1 Compressive stress distribution .....	30
2.4.2 Scaled damage factor distribution.....	32
2.4.3 DOP analysis.....	33
2.4.3.1 <i>Effect of compressive strength</i> .....	33
2.4.3.2 <i>Effect of striking velocity</i> .....	33

2.4.3.3	<i>Effect of CRH ratio</i>	34
2.4.3.4	<i>Proposed model to predict DOP</i>	35
2.4.4	Cratering damage analysis	37
2.4.4.1	<i>Effect of compressive strength</i>	37
2.4.4.2	<i>Effect of striking velocity</i>	38
2.5	Conclusions	39
	Acknowledgements	40
	References	41
<b>CHAPTER 3: EXPERIMENTAL AND NUMERICAL STUDIES OF ULTRA-HIGH PERFORMANCE CONCRETE TARGETS AGAINST HIGH-VELOCITY PROJECTILE IMPACTS</b>		<b>44</b>
	Abstract	44
3.1	Introduction	45
3.2	Preparation of UHPC targets	46
3.2.1	Materials	46
3.2.2	Manufacturing procedure	47
3.3	Material static tests	47
3.4	High-velocity impact tests	50
3.4.1	UHPC targets	50
3.4.2	Projectile	51
3.4.3	Test set-up	51
3.4.4	Results and discussions	53
3.4.4.1	<i>DOP analysis</i>	55
3.4.4.2	<i>Crater diameter analysis</i>	57
3.4.4.3	<i>Volume loss analysis</i>	58
3.4.4.4	<i>Projectile damage and abrasion</i>	59
3.5	Numerical simulations	60
3.5.1	Material models	61
3.5.1.1	<i>UHPC targets</i>	61
3.5.1.2	<i>Projectile</i>	63
3.5.2	Numerical models	64
3.5.3	Modelling results	64
3.5.3.1	<i>DOP comparison</i>	64

3.5.3.2	<i>An empirical model to predict DOP of UHPC targets</i>	64
3.5.3.3	<i>Crater diameter comparison</i>	66
3.5.3.4	<i>Projectile abrasion and damage comparison</i>	68
3.5.3.5	<i>Localized damages of UHPC targets</i>	69
3.5.3.6	<i>Energy evolution of projectile and UHPC targets</i>	70
3.6	Conclusions	71
	Acknowledgements	72
	References	72
<b>CHAPTER 4: EXPERIMENTAL AND NUMERICAL STUDY OF REACTIVE POWDER CONCRETE REINFORCED WITH STEEL WIRE MESH AGAINST PROJECTILE PENETRATION</b>		<b>77</b>
	Abstract	77
4.1	Introduction	78
4.2	Experimental program	80
4.2.1	Mix design of reactive powder concrete	80
4.2.2	Steel wire mesh	82
4.2.3	Projectiles	82
4.2.4	Static tests	83
4.2.5	High-velocity projectile impact test	85
4.2.6	Results and discussion	86
4.2.6.1	<i>Experimental data</i>	86
4.2.6.2	<i>DOP analysis</i>	88
4.2.6.3	<i>Crater dimensions analysis</i>	90
4.2.6.4	<i>Terminal ballistic trajectory</i>	92
4.2.6.5	<i>Projectile abrasion and damage</i>	93
4.3	Numerical simulation	94
4.3.1	RPC targets	94
4.3.2	Steel wire mesh	97
4.3.3	Projectile	98
4.3.4	Mesh size convergence	99
4.3.5	Results and discussion	100
4.3.5.1	<i>Histories of projectile penetration into RPC targets</i>	100
4.3.5.2	<i>DOP analysis</i>	103

4.3.5.3	<i>Cratering damage analysis</i> .....	104
4.3.5.4	<i>Projectile abrasion and damage</i> .....	106
4.4	Influence of steel wire mesh on the resistance of projectile penetration .....	106
4.5	Conclusion .....	114
	Acknowledgement.....	115
	References .....	115
<b>CHAPTER 5: NUMERICAL INVESTIGATION OF REACTIVE POWDER CONCRETE REINFORCED WITH STEEL WIRE MESH AGAINST HIGH-VELOCITY PROJECTILE PENETRATION .....</b>		<b>121</b>
	Abstract .....	121
5.1	Introduction .....	122
5.2	Numerical modelling.....	124
5.2.1	Material model for concrete .....	124
5.2.2	Material model for steel wire mesh.....	125
5.2.3	Material model for steel projectile .....	126
5.2.4	Numerical models setup .....	127
5.2.5	Validation of numerical models .....	131
5.2.5.1	<i>High-velocity impact test</i> .....	131
5.2.5.2	<i>Comparison of numerical and experimental results</i> .....	131
5.3	Parametric simulations and discussions .....	132
5.3.1	Working mechanism of steel wire mesh on confining concrete damage .....	133
5.3.2	DOP analysis .....	135
5.3.2.1	<i>Comparison of plain and reinforced RPC targets</i> .....	135
5.3.2.2	<i>Number of layers, N</i> .....	136
5.3.2.3	<i>Tensile strength of steel wires, <math>f_t</math></i> .....	136
5.3.2.4	<i>Diameter of steel wires, <math>d_o</math></i> .....	137
5.3.2.5	<i>Space between steel wires per layer, <math>d_1</math></i> .....	138
5.3.2.6	<i>Space between layers, <math>d_2</math></i> .....	138
5.3.2.7	<i>Empirical model for DOP</i> .....	139
5.3.3	Localized and crater damages analysis .....	142
5.3.3.1	<i>Comparison of plain and reinforced RPC targets</i> .....	143
5.3.3.2	<i>Number of layers, N</i> .....	144

5.3.3.3	<i>Tensile strength of steel wires, ft.....</i>	144
5.3.3.4	<i>Diameter of steel wires, do.....</i>	145
5.3.3.5	<i>Space between steel wires per layer, d1 .....</i>	146
5.3.3.6	<i>Space between layers, d2 .....</i>	147
5.3.4	Energy history analysis .....	148
5.3.4.1	<i>Number of layers, N .....</i>	149
5.3.4.2	<i>Tensile strength of steel wires, ft.....</i>	150
5.3.4.3	<i>Diameter of steel wires, do.....</i>	151
5.3.4.4	<i>Space between steel wires per layer, d1 .....</i>	152
5.3.4.5	<i>Space between layers, d2 .....</i>	152
5.4	Conclusions .....	153
	Acknowledgements .....	154
	References .....	154
<b>CHAPTER 6: CERAMIC BALLS PROTECTED ULTRA HIGH</b>		
<b>PERFORMANCE CONCRETE STRUCTURE AGAINST PROJECTILE</b>		
<b>IMPACT - A NUMERICAL STUDY.....159</b>		
	Abstract .....	159
6.1	Introduction .....	160
6.2	Numerical modelling.....	162
6.2.1	SPH formulation .....	162
6.2.2	Constitutive models of materials.....	164
6.2.3	Numerical models and configuration .....	168
6.2.4	SPH-FE coupling and contact definitions .....	173
6.3	Validation of numerical models .....	175
6.3.1	High-velocity impact test on thin UHPC slabs .....	175
6.3.2	High-velocity impact test on thick UHPC slabs .....	176
6.3.3	Effects of major parameters .....	176
6.3.3.1	<i>Effect of SPH domain size.....</i>	178
6.3.3.2	<i>Effect of SPH particle distance .....</i>	178
6.3.3.3	<i>Effect of SPH particle approximation theory (FORM) .....</i>	179
6.3.3.4	<i>Effect of smooth length constant (CSLH).....</i>	179
6.3.3.5	<i>Effect of the sensitivity of material parameters.....</i>	180

6.3.3.6	<i>Determination of other parameters</i> .....	181
6.3.4	Model comparison with experimental results .....	181
6.4	Numerical results and discussions .....	183
6.4.1	Perforation of ceramic balls protected thin UHPC slabs .....	185
6.4.1.1	<i>Perforation process and energy history</i> .....	185
6.4.1.2	<i>Effect of arrangement of ceramic balls</i> .....	187
6.4.1.3	<i>Comparison between Al<sub>2</sub>O<sub>3</sub> and SiC ceramic balls</i> .....	189
6.4.1.4	<i>Effect of impact positions</i> .....	190
6.4.1.5	<i>Effect of diameter of ceramic balls</i> .....	192
6.4.1.6	<i>Perforation and ballistic limits of protected targets</i> .....	193
6.4.2	DOP analysis of ceramic balls protected thick UHPC slabs.....	195
6.5	Conclusions .....	197
	Acknowledgements .....	198
	References .....	198
	<b>CHAPTER 7: CONCLUSIONS AND RECOMMENDATIONS</b> .....	<b>206</b>
7.1	Major findings .....	206
7.1.1	UHPC .....	206
7.1.2	Steel wire mesh reinforced RPC .....	207
7.1.3	Ceramic balls protected UHPC .....	208
7.2	Recommendations for future work.....	209



## LIST OF FIGURES

<b>Figure 2.1:</b> Setup of uniaxial compression test (a) real test (b) numerical simulation ..	20
<b>Figure 2.2:</b> Comparison of experimental and numerical compressive stress and strain curves .....	21
<b>Figure 2.3:</b> Setup of four-point bending test (a) real test (b) numerical simulation .....	21
<b>Figure 2.4:</b> Comparison of test and numerical load and displacement curves at mid-span.....	22
<b>Figure 2.5:</b> Schemes of ogive-nosed projectile (a) dimensions (b) numerical model....	23
<b>Figure 2.6:</b> UHPC targets dimensions .....	24
<b>Figure 2.7:</b> K&C concrete model (a) three shear surfaces (b) concrete constitutive behaviour [14] .....	25
<b>Figure 2.8:</b> The relationship between $\lambda$ and $\eta$ .....	26
<b>Figure 2.9:</b> DIF for UHPC in tension and compression.....	29
<b>Figure 2.10:</b> Development of compressive stress in UHPC (130 MPa) at 800 m/s (a) $t = 90 \mu s$ (b) $t = 240 \mu s$ (c) $t = 400 \mu s$ (d) $t = 520 \mu s$ .....	31
<b>Figure 2.11:</b> Development of scaled damage factor in UHPC (130 MPa) at 675 m/s (a) $t = 90 \mu s$ (b) $t = 240 \mu s$ (c) $t = 400 \mu s$ (d) $t = 520 \mu s$ .....	33
<b>Figure 2.12:</b> DOP versus striking velocity of projectile for UHPC targets with various compressive strengths.....	34
<b>Figure 2.13:</b> DOP versus CRH ratios of projectile for 170 MPa UHPC at 550 m/s.....	35
<b>Figure 2.14:</b> The abridged sketch of the ogive-nosed projectile.....	36
<b>Figure 2.15:</b> Simulation data and prediction of DOP/d versus striking velocity of projectile using proposed model and modified NDRC formula for UHPC targets (a) 190 MPa (b) 170 MPa (c) 130 MPa (d) 90 MPa.....	37
<b>Figure 2.16:</b> Cratering damage versus compressive strength of UHPC targets at 300 m/s (a) 90 MPa (b) 130 MPa (c) 170 MPa (d) 190 MPa.....	38
<b>Figure 2.17:</b> Cratering damage versus striking velocity of projectile for 190 MPa UHPC targets (a) 300 m/s (b) 550 m/s (c) 675 m/s (d) 800 m/s (e) 1000 m/s .....	39
<b>Figure 2.18:</b> Crater dimensions versus CRH ratio of projectile for 170 MPa UHPC targets at 550 m/s (a) CRH=3 (b) CRH=2 (c) CRH=1 .....	39

<b>Figure 3.1:</b> Typical compressive failure modes (a) plain concrete (b) UHPC-PF (c) UHPC-SF .....	48
<b>Figure 3.2:</b> Compressive stress and strain curves .....	49
<b>Figure 3.3:</b> Typical flexural failure modes of specimens (a) plain concrete (b) UHPC-PF (c) UHPC-SF.....	50
<b>Figure 3.4:</b> Lateral force and displacement curves .....	50
<b>Figure 3.5:</b> Cylindrical concrete targets .....	51
<b>Figure 3.6:</b> Schemes of ogive-nosed projectile .....	51
<b>Figure 3.7:</b> High-velocity impact test setup .....	52
<b>Figure 3.8:</b> Photographs of typical projectile penetration into UHPC-SF-3 target at 808 m/s (a) 0 $\mu$ s (b) 50 $\mu$ s (c) 100 $\mu$ s (d) 150 $\mu$ s .....	53
<b>Figure 3.9:</b> Localized damages of targets (a) PC-1 (b) PC-2 (c) PC-3 (d) UHPC-PF-1 (e) UHPC-PF-2 (f) UHPC-PF-3 (g) UHPC-SF-1 (h) UHPC-SF-2 (i) UHPC-SF-3 .....	54
<b>Figure 3.10:</b> Measurement of average crater diameter .....	54
<b>Figure 3.11:</b> DOP versus striking velocity of projectile .....	56
<b>Figure 3.12:</b> The crater diameter versus striking velocity of projectile .....	58
<b>Figure 3.13:</b> The volume loss versus striking velocity of projectile .....	59
<b>Figure 3.14:</b> Projectile damages and abrasions after tests (a) plain concrete targets (b) UHPC-PF targets (c) UHPC-SF targets.....	60
<b>Figure 3.15:</b> Numerical setup for the projectile impact test.....	60
<b>Figure 3.16:</b> DIF for UHPC in tension and compression.....	62
<b>Figure 3.17:</b> Test, simulation and proposed models of DOP versus the striking velocity of projectile (a) UHPC-PF targets (b) UHPC-SF targets .....	65
<b>Figure 3.18:</b> Crater diameter of UHPC-PF targets.....	67
<b>Figure 3.19:</b> Crater diameter of UHPC-SF targets.....	67
<b>Figure 3.20:</b> Comparison of crater diameter between numerical simulation and test (a) UHPC-PF targets (b) UHPC-SF targets.....	68
<b>Figure 3.21:</b> Comparison of projectile abrasions and damages between numerical and test results .....	68
<b>Figure 3.22:</b> Localized damages (a) UHPC-PF-1 (b) UHPC-PF-2 (c) UHPC-PF-3 .....	69
<b>Figure 3.23:</b> Localized damages (a) UHPC-SF-1 (b) UHPC-SF-2 (c) UHPC-SF-3 .....	70

<b>Figure 3.24:</b> Energy histories of projectiles and UHPC targets (a) ~550 m/s (b) ~675 m/s (c) ~800 m/s.....	71
<b>Figure 4.1:</b> Cylindrical RPC targets.....	81
<b>Figure 4.2:</b> Design details of each layer steel mesh.....	82
<b>Figure 4.3:</b> Schemes of the projectile.....	83
<b>Figure 4.4:</b> Uniaxial compression test (a) set-up (b) stress and strain curve .....	84
<b>Figure 4.5:</b> Four-point bending test (a) set-up (b) force and displacement curve of specimen.....	85
<b>Figure 4.6:</b> Projectile penetration into RPC targets (a) powder gun (b) test set-up.....	86
<b>Figure 4.7:</b> Photographs of typical projectile penetration at 679 m/s (a) 0 $\mu$ s (b) 50 $\mu$ s (c) 100 $\mu$ s (d) 150 $\mu$ s.....	86
<b>Figure 4.8:</b> Localized damage of RPC targets (a) 539 m/s (b) 679 m/s (c) 807 m/s .....	87
<b>Figure 4.9:</b> Measurement of average crater diameter .....	88
<b>Figure 4.10:</b> DOP versus striking velocity of projectile .....	90
<b>Figure 4.11:</b> The inner crater diameter versus striking velocity of projectile.....	91
<b>Figure 4.12:</b> The outer cratering damage diameter versus striking velocity of projectile.....	91
<b>Figure 4.13:</b> The volume loss versus striking velocity of projectile.....	92
<b>Figure 4.14:</b> Terminal ballistic trajectory at striking velocity of 807 m/s .....	92
<b>Figure 4.15:</b> Abrasions and damage of projectiles against striking velocities of 539 m/s, 679 m/s and 807 m/s.....	93
<b>Figure 4.16:</b> Numerical model of cylindrical RPC target .....	94
<b>Figure 4.17:</b> DIFs for RPC in (a) compression (b) tension.....	96
<b>Figure 4.18:</b> 44-layer steel wire meshes.....	97
<b>Figure 4.19:</b> Numerical model of projectile.....	98
<b>Figure 4.20:</b> Comparisons of residual velocities with three various mesh sizes.....	99
<b>Figure 4.21:</b> Development of scaled damage factor in concrete target at 539 m/s (a) $t=110 \mu$ s (b) $t=180 \mu$ s (c) $t=300 \mu$ s (d) $t=420 \mu$ s .....	101
<b>Figure 4.22:</b> Numerical and experimental investigation of terminal ballistic trajectory of projectile at striking velocity of 807 m/s .....	101
<b>Figure 4.23:</b> Velocity and displacement histories of projectile penetration into concrete targets at 539 m/s, 679 m/s and 807 m/s.....	102
<b>Figure 4.24:</b> Kinetic and internal energy history at 807 m/s.....	103

<b>Figure 4.25:</b> Comparison of internal energy of steel wire meshes at various striking velocities.....	103
<b>Figure 4.26:</b> Comparison between experimental and numerical results of DOP at striking velocities of 539 m/s, 679 m/s and 807 m/s .....	104
<b>Figure 4.27:</b> Cratering damage versus various striking velocities of 539 m/s, 679 m/s and 807 m/s.....	105
<b>Figure 4.28:</b> Comparison between experimental and numerical results of cratering damage diameter at striking velocities of 539 m/s, 679 m/s and 807 m/s .....	105
<b>Figure 4.29:</b> Localized damage of projectile at striking velocities of 539 m/s, 679 m/s and 807 m/s.....	106
<b>Figure 4.30:</b> Configuration of parallel 44-layer steel wire meshes.....	107
<b>Figure 4.31:</b> Design details of each layer steel wire mesh (a) $\phi$ 2 mm with 6 mm space (b) $\phi$ 1 mm with 12 mm space .....	108
<b>Figure 4.32:</b> Design details of spiral steel wire mesh (a) 44-layer and 3 mm space between layers (b) 22-layer and 3 mm space between layers (c) 22-layer and 6 mm space between layers .....	109
<b>Figure 4.33:</b> Localized damages for reinforced RPC targets (a) Type 1 (b) Type 2 (c) Type 3 (d) Type 4 (e) Type 5 (f) Type 6 (g) Type 7 (h) Type 8.....	111
<b>Figure 4.34:</b> DOPs for various types of reinforced RPC targets after projectile penetration .....	112
<b>Figure 4.35:</b> Energy evolution of steel wire mesh for various types of reinforced RPC targets.....	113
<b>Figure 5.1:</b> Geometry of cylindrical RPC target .....	127
<b>Figure 5.2:</b> Design details of each layer steel wire meshes (a) $\phi$ 1 mm with 3 mm space (b) $\phi$ 1 mm with 6 mm space (c) $\phi$ 1 mm with 12 mm space (d) $\phi$ 0.5 mm with 6 mm space (e) $\phi$ 2 mm with 6 mm space .....	129
<b>Figure 5.3:</b> Design details of spiral steel wire meshes $\phi$ 1 mm with (a) 44-layer and 3 mm space between layers (b) 33-layer and 3 mm space between layers (c) 22-layer and 3 mm space between layers (d) 11-layer and 3 mm space between layers (e) 22-layer and 5 mm space (f) 22-layer and 6 mm space between layers .....	130
<b>Figure 5.4:</b> Schemes of the projectile.....	130

<b>Figure 5.5:</b> Setup of high-velocity impact test.....	131
<b>Figure 5.6:</b> Impact response of steel wire mesh in resisting projectile penetration at 807 m/s (a) side view in numerical simulation (b) front view in test.....	134
<b>Figure 5.7:</b> Comparison of DOP for plain and RPC targets reinforced with 44-layer steel wire meshes.....	135
<b>Figure 5.8:</b> DOP versus number of layers.....	136
<b>Figure 5.9:</b> DOP versus tensile strength of steel wires .....	137
<b>Figure 5.10:</b> DOP versus diameter of steel wires.....	137
<b>Figure 5.11:</b> DOP versus space between steel wires per layer.....	138
<b>Figure 5.12:</b> DOP versus space between layers .....	139
<b>Figure 5.13:</b> Proposed model to predict DOP versus (a) striking velocity for plain RPC targets (b) compressive strength of RPC targets (c) number of layers of steel wire meshes (d) tensile strength of steel wires (e) diameter of steel wires (f) space between steel wires per layer (g) space between layers .....	141
<b>Figure 5.14:</b> Comparison of DOP between the test results and the proposed model in the present study.....	142
<b>Figure 5.15:</b> Localized damages at 679 m/s (a) plain RPC (b) reinforced RPC (44-layer, parallel) (c) reinforced RPC (44-layer, spiral) .....	143
<b>Figure 5.16:</b> Cratering damages for the protected part of RPC targets at 679 m/s (a) Type 2 (b) Type 5 (c) Type 7 .....	143
<b>Figure 5.17:</b> Localized damages versus number of layers at 679 m/s (a) 44-layer (b) 33-layer (c) 22-layer (d) 11-layer.....	144
<b>Figure 5.18:</b> Cratering damages on the protected part of RPC targets versus number of layers at 679 m/s (a) Type 7 (b) Type 10 (c) Type 11 (d) Type 14 ....	144
<b>Figure 5.19:</b> Localized damages versus tensile strength of steel wires at 679 m/s (a) 400 MPa (b) 785 MPa (c) 1285 MPa (d) 1725 MPa.....	145
<b>Figure 5.20:</b> Cratering damages on the protected part of RPC targets versus tensile strength of steel wires at 679 m/s (a) Type 7 (b) Type 19 (c) Type 20 (d) Type 21 .....	145
<b>Figure 5.21:</b> Localized damages versus diameter of steel wires at 679 m/s (a) 0.5 mm (b) 1 mm (c) 2 mm .....	146

<b>Figure 5.22:</b> Cratering damages versus diameter of steel wires for the protected part of RPC targets at 679 m/s (a) Type 24 (b) Type 25 (c) Type 28.....	146
<b>Figure 5.23:</b> Localized damages versus space between steel wires per layer at 679 m/s (a) 6 mm (b) 3 mm (c) 12 mm .....	147
<b>Figure 5.24:</b> Cratering damages versus the space between steel wires per layer for the protected part of RPC targets at 679 m/s (a) Type 7 (b) Type 15 (c) Type 18.....	147
<b>Figure 5.25:</b> Localized damages versus space between layers at 679 m/s (a) 3 mm (b) 6 mm (c) 5 mm .....	148
<b>Figure 5.26:</b> Cratering damages versus space between layers for the protected part of RPC targets at 679 m/s (a) Type 11 (b) Type 25 (c) Type 31.....	148
<b>Figure 5.27:</b> Kinetic, internal and hourglass energy histories at 679 m/s.....	149
<b>Figure 5.28:</b> Energy change versus number of layers at 679 m/s (a) kinetic energy of projectile (b) internal energy of steel wire meshes .....	150
<b>Figure 5.29:</b> Energy change versus tensile strength of steel wires at 679 m/s (a) kinetic energy of projectile (b) internal energy of steel wire meshes .....	151
<b>Figure 5.30:</b> Energy change versus diameter of steel wires at 679 m/s (a) kinetic energy of projectile (b) internal energy of steel wire meshes .....	151
<b>Figure 5.31:</b> Energy change versus space between steel wires per layer at 679 m/s (a) kinetic energy of projectile (b) internal energy of steel wire meshes .....	152
<b>Figure 5.32:</b> Energy change versus space between layers at 679 m/s (a) kinetic energy of projectile (b) internal energy of steel wire meshes .....	153
<b>Figure 6.1:</b> Tensile characteristics of UHPC in the present study (a) lateral forced displacement curve (b) predicted uniaxial tensile stress strain curve .....	165
<b>Figure 6.2:</b> Numerical setup (a) 50 mm thick UHPC slabs with D20 mm ceramic balls (b) 50 mm thick UHPC slabs with D40 ceramic balls (c) 50 mm thick UHPC slabs with D60 ceramic balls (d) 350 mm thick UHPC slabs with D20 ceramic balls.....	170
<b>Figure 6.3:</b> Configurations of ceramic balls (a) hex-pack, D60, 2 layers (b) checkerboard, D40, 3 layers (c) hex-pack, D40, 3 layers (d) hex-pack, D20, 6 layers .....	171
<b>Figure 6.4:</b> Schematic diagram of the ogive-nosed projectile .....	172
<b>Figure 6.5:</b> Single ceramic ball (a) D60 (b) D40 (c) D20 .....	172

<b>Figure 6.6:</b> Impact positions of ceramic balls .....	173
<b>Figure 6.7:</b> Coupled SPH particles and Lagrangian solid elements for UHPC slabs ..	174
<b>Figure 6.8:</b> SPH-FE contact calculation cycle [57].....	174
<b>Figure 6.9:</b> Schematic diagram of high-velocity impact test on thin UHPC slabs [6].	175
<b>Figure 6.10:</b> Setup of high-velocity impact test on thick UHPC slabs [4].....	176
<b>Figure 6.11:</b> Influence of major parameters (a) SPH domain size (b) SPH particle size (c) SPH particle approximation theory (d) smooth length constant.	177
<b>Figure 6.12:</b> Numerical and experimental projectile impact process with fragmentation (a) 70 mm thick UHPC slab, 348 m/s (Test 1-6) [6] (b) 700 mm thick UHPC target, 808 m/s (Test 2-3) [4].....	182
<b>Figure 6.13:</b> Comparison between experimental and numerical results (a) residual velocity of projectile versus thickness of slab at ~350 m/s (b) residual velocity of projectile versus striking velocity of projectile for 50 mm thick UHPC slabs (c) DOP versus striking velocity of projectile for thick UHPC slabs .....	183
<b>Figure 6.14:</b> Projectile perforation process into D40 ceramic balls protected thin UHPC slab in the hex-pack arrangement at impact position 3 at 800 m/s (Test 20).....	185
<b>Figure 6.15:</b> Localized damages of the hex-pack arrangement of D40 ceramic balls (Test 20) per layer at 800m/s at 270 $\mu$ s .....	186
<b>Figure 6.16:</b> Impact response of the steel case (Test 20) at 270 $\mu$ s at 800 m/s (a) front surface (b) rear surface .....	186
<b>Figure 6.17:</b> Impact response of D40 ceramic balls protected thin UHPC slab in the hex-pack arrangement at impact position 3 at 800 m/s (Test 20) (a) impact resistance (b) energy evolution.....	187
<b>Figure 6.18:</b> Projectile perforation into D40 ceramic balls protected thin UHPC slab in the checkerboard arrangement at impact position 3 at 800 m/s (Test 24) .....	188
<b>Figure 6.19:</b> Impact response of D40 ceramic balls protected thin UHPC slab in various arrangements at impact position 3 at 800 m/s (a) impact resistance (b) residual velocity of projectile.....	188



<b>Figure 6.20:</b> Comparison between D20 Al <sub>2</sub> O <sub>3</sub> and SiC ceramic balls at impact position 3 at 800 m/s (a) impact resistance (b) residual velocity of projectile .....	190
<b>Figure 6.21:</b> Impact response of D60 ceramic balls protected thin UHPC slab at various impact positions at 800 m/s (a) impact resistance (b) residual velocity of projectile .....	191
<b>Figure 6.22:</b> Impact response of D40 ceramic balls protected thin UHPC slab at various impact positions at 800 m/s (a) impact resistance (b) residual velocity of projectile .....	191
<b>Figure 6.23:</b> Impact response of D20 ceramic balls protected thin UHPC slab at various impact positions at 800 m/s (a) impact resistance (b) residual velocity of projectile .....	191
<b>Figure 6.24:</b> Projectile perforation process into D20 ceramic balls protected thin UHPC slab in the hex-pack arrangement at impact position 3 at 800 m/s (Test 30) .....	192
<b>Figure 6.25:</b> Projectile perforation process into D60 ceramic balls protected thin UHPC slab in the hex-pack arrangement at impact position 3 at 800 m/s (Test 9) .....	192
<b>Figure 6.26:</b> Comparison of projectile perforation of thin UHPC slabs protected with D20, D40 and D60 ceramic balls (a) impact resistance (b) residual velocity of projectile .....	193
<b>Figure 6.27:</b> Residual velocity of projectile versus layers of ceramic balls at 800 m/s .....	194
<b>Figure 6.28:</b> The relations among residual kinetic energy, kinetic energy dissipation and initial kinetic energy of projectiles .....	195
<b>Figure 6.29:</b> Projectile penetration of thick UHPC slabs with 6-layer hex-pack arranged D20 ceramic balls at different striking velocities (a) 550 m/s (b) 675 m/s (c) 800 m/s .....	196
<b>Figure 6.30:</b> DOP versus striking velocity of projectile .....	197



## LIST OF TABLES

<b>Table 2.1:</b> Mix proportions of UHPC (unit:kg) .....	19
<b>Table 2.2:</b> Material properties of UHPC .....	20
<b>Table 2.3:</b> Key inputs for the casing of projectile .....	24
<b>Table 2.4:</b> Key inputs for Mat_72R3 .....	28
<b>Table 2.5:</b> Penetration tests data of DOP .....	30
<b>Table 3.1:</b> Mix proportions of UHPC (unit: kg) .....	47
<b>Table 3.2:</b> Material properties of fibres.....	47
<b>Table 3.3:</b> High-velocity impact test data .....	55
<b>Table 3.4:</b> Key inputs for Concrete Damage Rel3 .....	61
<b>Table 3.5:</b> Material parameters for casing of projectile .....	63
<b>Table 3.6:</b> Material parameters for backfill of projectile .....	63
<b>Table 3.7:</b> Comparison of DOP among experiments, numerical simulation and proposed models .....	66
<b>Table 4.1:</b> Mix proportions of RPC (unit: kg).....	81
<b>Table 4.2:</b> High-velocity impact test data .....	88
<b>Table 4.3:</b> Key inputs for Mat_72R3 .....	95
<b>Table 4.4:</b> Material parameters for steel wire mesh.....	98
<b>Table 4.5:</b> Material parameters for casing of projectile .....	98
<b>Table 4.6:</b> Material parameters for backfill of projectile .....	99
<b>Table 4.7:</b> Numerical test plan .....	107
<b>Table 5.1:</b> Key inputs for 100 MPa RPC targets.....	125
<b>Table 5.2:</b> Material parameters for steel wire meshes.....	126
<b>Table 5.3:</b> Material parameters for casing of projectile .....	126
<b>Table 5.4:</b> Comparison of experimental and numerical results.....	132
<b>Table 5.5:</b> Numerical test plan and results .....	133
<b>Table 6.1:</b> Parameters of Mat_111 for UHPC material.....	166
<b>Table 6.2:</b> Mechanical properties and parameters in JH-2 model for ceramic balls....	167
<b>Table 6.3:</b> Material parameters for the steel projectile and case.....	168
<b>Table 6.4:</b> Contact type for each part .....	175
<b>Table 6.5:</b> Comparison of numerical results for different parameters .....	177
<b>Table 6.6:</b> Sensitivity of material parameters of UHPC on Vr and DOP .....	181

<b>Table 6.7:</b> Comparison of experimental and numerical results.....	182
<b>Table 6.8:</b> Numerical results for UHPC slabs protected with ceramic balls.....	184

## ABSTRACT

In recent decades, terrorism activities are becoming increasingly more frequent throughout the world. Terrorist attacks that target military and civil buildings will not only cause structural damages, but also lead to massive casualties and property loss. Therefore, the development of new construction materials with excellent performance to resist extreme loadings has been attracting much attention from researchers and engineers.

Evolving from reactive powder concrete (RPC), novel ultra-high performance concrete (UHPC) materials with nano-material and fibre addition have been developed by many universities and government agencies in these years. With the purpose of enriching the knowledge of UHPC materials subjected to high-velocity projectile penetration, this thesis presents a number of experimental and numerical research findings on UHPC materials in journals.

Prior to real high-velocity projectile impact tests, numerical approaches in simulating the impact response of UHPC targets under projectile penetration are presented. The numerical models of UHPC targets are validated against the uniaxial compressive and four-point bending testing results. With the validated numerical models incorporating dynamic increase factors (DIF), parametric studies on the effects of target compressive strength, projectile striking velocity and projectile Calibre Radius Head (CRH) ratio on depth of penetration (DOP) and crater diameter of UHPC targets are discussed. Based on the simulation data on DOP, an empirical model to predict DOP of UHPC targets is proposed.

High-velocity projectile impact tests are then conducted on UHPC targets reinforced with 3 Vol-% ultra-high molecular weight polyethylene (UHMWPE) fibres and UHPC targets with 3 Vol-% steel fibres. Under the same loading scenarios, plain concrete targets without the addition of fibres are also tested as control specimens for comparative purpose. Dynamic behaviours of concrete targets involving DOP, crater diameter, volume loss as well as abrasions and damages of projectiles after impact are observed and compared with the numerical results. Also, DOPs of UHPC targets are compared with the previously proposed empirical model and the fair agreement is achieved in terms of UHPC targets with steel fibres.

Although UHPC reinforced with steel fibres has been a promising material with excellent impact resistance which can be directly used in the structural components in civil and military constructions, the high cost of steel fibres may limit the use of UHPC in military and civil constructions, so an extended investigation of steel wire meshes with relatively low cost to replace steel fibres in UHPC is necessary. In this thesis, the impact responses of 44-layer steel wire meshes reinforced RPC targets such as DOP, crater diameter, volume loss as well as abrasions and damages of projectiles after impact are investigated under the same loading environment as UHPC targets.

In order to comprehensively understand the effects of steel wire meshes on the impact response of reinforced RPC targets, parametric studies are conducted after validating numerical models, in which the variables include configuration of whole steel wire meshes, number of layers, space between two layers, space between two steel wires per layer as well as the diameter and tensile strength of steel wires. Based on the results of parametric studies, an empirical model derived from the simulation data is proposed to predict DOP of reinforced RPC targets.

Simultaneously, optimal structural designs with effective reinforcement configurations are under extensive investigation to enhance the impact performance of UHPC targets. A numerical approach is used to investigate the impact response of uniformly distributed ceramic balls as a shielding structure on UHPC targets under high-velocity projectile penetration. Parametric studies are conducted on thin UHPC slabs to explore the influence of impact location, diameter, spatial arrangement and material properties of ceramic balls on impact response. Perforation and ballistic limits of ceramic balls protected thin UHPC slabs are obtained. Besides, DOPs of thick UHPC slabs protected with 6-layer ceramic balls with a diameter of 20 mm in a hex-pack arrangement are compared with existing UHPC targets.

## **ACKNOWLEDGEMENTS**

The author would like to express his deepest gratitude to his principle supervisor, Prof. Chengqing Wu, for his patience, support, frankness, invaluable guidance and constructive suggestions in the doctoral study. The author would also express his sincerest gratitude to his co-supervisor, Dr. Jun Li, for his encouragement and enlightening suggestions. Special thanks are also given to Dr. Yu Su, who has made a great contribution to the development of materials used in the present research work. Simultaneously, many thanks are given to the author's colleagues for helping with the improvement of the work. This research would not be a success without their supervisions and advice.

The author extends his sincerest thanks to his family for the support, especially his father, Mr. Jinming Liu, and mother, Mrs. Qinglian Luo. Also, his elder sister, Mrs. Li Liu, brother in law, Mr. Xiao Liu and nephew, Jiayi Liu, deserve lots of thanks and much more for their support. Finally, the author dedicates this thesis to his wife, Mrs. Lianjun Liu, and his unborn daughter, Jia'er Liu, who have provided the author with the confidence and support.

## LIST OF PUBLICATIONS

- 1) Liu, J., Wu, C., Li, J., Su, Y., Shao, R., Liu, Z. and Chen, G., 2017. Experimental and numerical study of reactive powder concrete reinforced with steel wire mesh against projectile penetration. *International Journal of Impact Engineering* (**Impact Factor: 2.938**), 109, pp.131-149.  
**Status:** Published
- 2) Liu, J., Wu, C., Su, Y., Li, J., Shao, R., Chen, G. and Liu, Z., 2018. Experimental and numerical studies of ultra-high performance concrete targets against high-velocity projectile impacts. *Engineering Structures* (**Impact Factor: 2.755**), 173, pp.166-179.  
**Status:** Published
- 3) Liu, J., Wu, C. and Chen, X., 2017. Numerical study of ultra-high performance concrete under non-deformable projectile penetration. *Construction and Building Materials* (**Impact Factor: 3.169**), 135, pp.447-458.  
**Status:** Published
- 4) Liu, J., Wu, C., Li, J., Su, Y. and Chen, X., 2018. Numerical investigation of reactive powder concrete reinforced with steel wire mesh against high-velocity projectile penetration. *Construction and Building Materials* (**Impact Factor: 3.169**), 166, pp.855-872.  
**Status:** Published
- 5) Liu, J., Wu, C., Li, J., Fang, J. and Su, Y., 2018. A novel structure of ceramic balls reinforced ultra high performance concrete targets under projectile impacts.  
**Status:** Submitted to *International Journal of Impact Engineering* (**Impact Factor: 2.938**)